

1 **Validation of large-scale solar reactors for the treatment of rainwater in field trials in sub-**  
2 **Saharan Africa**

3 B. Reyneke<sup>a</sup>, T. Ndlovu<sup>a</sup>, M.B. Vincent<sup>b</sup>, A. Martinez-Garcia<sup>c</sup>, M.I. Polo-López<sup>c</sup>, P. Fernández-  
4 Ibáñez<sup>c,d</sup>, G. Ferrero<sup>e</sup>, S. Khan<sup>f</sup>, K.G. McGuigan<sup>g</sup> and W. Khan<sup>a\*</sup>

5

6 <sup>a</sup> Department of Microbiology, Faculty of Science, Stellenbosch University, Private Bag X1,  
7 Stellenbosch, 7602, South Africa.

8 <sup>b</sup> Ecosystem Environmental Services S.A., Sant Andreu de Llavaneres, Barcelona, Spain.

9 <sup>c</sup> Plataforma Solar de Almería-CIEMAT, P.O. Box 22, Tabernas, Almería, Spain.

10 <sup>d</sup> Nanotechnology and Integrated BioEngineering Centre, School of Engineering, University of Ulster,  
11 Newtownabbey, Northern Ireland, United Kingdom.

12 <sup>e</sup> IHE Delft Institute for Water Education, Westvest 7, 2611, AX, Delft, the Netherlands.

13 <sup>f</sup> Faculty of Health Sciences, University of Johannesburg, PO Box 17011, Doornfontein, 2028, South  
14 Africa.

15 <sup>g</sup> Department of Physiology and Medical Physics, Royal College of Surgeons in Ireland, Dublin,  
16 Ireland.

17

18 Short title: Large-scale SODIS treatment of rainwater

19

20 Abbreviations<sup>1</sup>

21 \*Corresponding Author: Wesaal Khan; Phone: +27218085804; Fax: +27218085846; Email:

22 [wesaal@sun.ac.za](mailto:wesaal@sun.ac.za)

---

<sup>1</sup> ADWG – Australian drinking water guidelines; BDL – below detection limit; CFU – colony forming units; CPC – compound parabolic collector; DNA – deoxyribonucleic acid; DWAF – Department of Water Affairs and Forestry; *E. coli* – *Escherichia coli*; EMA – ethidium monoazide bromide; EU – European Union; FF – first-flush; HPC – heterotrophic plate count/heterotrophic bacteria; LB – luria bertani; PCA – principle component analysis; PET – polyethylene-terephthalate; PMA – propidium monoazide; PMMA – poly(methyl methacrylate); qPCR – quantitative polymerase chain reaction; RHRW – roof-harvested rainwater; ROS – reactive oxygen species; RWH – rainwater harvesting; SABS – South African Bureau of Standards; SODIS – solar disinfection; UV – ultraviolet radiation; WATERSPOUTT – Water Sustainable Point-Of-Use Treatment Technologies; WHO – World Health Organisation; WSP – water safety plan; Zn – zinc.

## Abstract

The efficiency of two large-scale solar reactors [Prototype I (140 L) and II (88 L)] in treating rainwater on-site in a local informal settlement (~~Site 1~~) and farming community (~~Site 2~~) was assessed. Untreated (~~Tank 1 and Tank 2 FF~~) and treated (Prototype I and II) tank water samples were routinely collected from each site and all the measured physico-chemical parameters, anions and cations were within national and international drinking water guidelines limits. Culture-based analysis indicated that *Escherichia coli*, total and faecal coliforms, enterococci and heterotrophic bacteria counts exceeded drinking water guideline limits in 61%, 100%, 45%, 24% and 100% of the untreated tank water samples collected from both sites. However, an 8 hour solar exposure treatment for both solar reactors was sufficient to reduce these indicator organisms to within drinking water standards, with the exception of the heterotrophic bacteria which exceeded the drinking water guideline limit in 43% of the samples treated with the Prototype I reactor (1.01 log reduction). Molecular viability analysis subsequently indicated that mean overall reductions of 75% and 74% were obtained for the analysed indicator organisms (*E. coli* and enterococci) and opportunistic pathogens (*Klebsiella*, *Legionella*, *Pseudomonas*, *Salmonella* and *Cryptosporidium* oocysts) in the Prototype I and II solar reactors, respectively. The large-scale solar reactor prototypes could thus effectively provide three (88 L Prototype II) to five (144 L Prototype I) people on a daily basis with the basic water requirement for human activities (25 L). Additionally, the outlined water safety plan may aid in identifying how and where rainwater harvesting systems should be installed and maintained to ensure the quality of the treated water.

**Keywords:** Rainwater harvesting; solar disinfection; rainwater quality; sub-Saharan Africa

## 46 1. Introduction

47 The Global Risks Report released for 2019 listed water crises as one of the top ten risks in  
48 terms of likelihood (rating of 9; very likely to occur) and impact (rating of 4; severe impact)  
49 (Global Risks Report, 2019). The probability of a water crisis risk in sub-Saharan Africa is  
50 significantly increased as a high proportion of the population reside in urban informal  
51 settlements and rural areas, with limited access to a safe water supply and sanitation  
52 infrastructure (Dos Santos et al. 2017). However, as highlighted by Gwenzi and Nyamadzawo  
53 (2014) and Emenike et al. (2017), rainwater is considered an under-exploited water source in  
54 sub-Saharan Africa and may serve as an effective reserve to improve and encourage equity  
55 in water access. Roof-harvested rainwater (RHRW) can however, be contaminated with  
56 various chemicals and microorganisms, which may limit its use as a potable water source  
57 (Hamilton et al. 2019). While the chemical pollutants have not been directly associated with  
58 the incidence of disease, organic debris and faecal matter from animals and birds that have  
59 access to the catchment surface, have been identified as the primary sources of microbial  
60 contaminants such as *Legionella*, *Klebsiella*, *Pseudomonas* and *Cryptosporidium* (Hamilton  
61 et al. 2019).

62 Treatment strategies that may be implemented to improve the quality of rainwater  
63 include the utilisation of gutter screens or first-flush diverters for the prevention of contaminant  
64 entry into the collection tank or post-collection treatment [chemical (e.g. chlorination) and  
65 physical treatments (e.g. filtration, solar disinfection (SODIS) and thermal disinfection)]  
66 (Hamilton et al. 2019). Although various chemical and physical treatment technologies have  
67 been investigated, SODIS is considered a cost-effective treatment method and is  
68 recommended by the World Health Organisation (WHO) for the effective reduction of microbial  
69 contamination in water sources (Ubomba-Jaswa et al. 2010). In its simplest form, SODIS  
70 entails filling a transparent container [usually a 2 L ~~or 5 L~~ polyethylene-terephthalate (PET)  
71 bottle] with contaminated water and exposing the bottle to direct sunlight for six to eight hours  
72 to allow ultraviolet (UV) radiation and solar-mild heat to inactivate microbial contaminants

73 (McGuigan et al. 2012). Ultraviolet radiation directly inactivates the microbial contaminants by  
74 damaging nucleic acids and leads to the formation of reactive oxygen species (ROS), which  
75 react and damage proteins, nucleic acids and membrane lipids (Nelson et al. 2018). The water  
76 temperature will also increase as water molecules absorb the UV radiation, which leads to cell  
77 membrane damage. The major drawbacks associated with this technique are however, the  
78 small volumes of water that can effectively be treated (2 to 5 L) and decreased efficiency  
79 during overcast weather conditions (up to 48 hours of treatment). Increases in treatment  
80 volume and efficiency may then be obtained by employing various modifications (SODIS  
81 enhancement technologies) such as solar mirrors (concentrates UV radiation) and larger  
82 reactor tubes (increase treatment volume) (Ubomba-Jaswa et al. 2010; McGuigan et al. 2012).

83 As part of the European Union (EU) Horizon 2020 project titled Water Sustainable  
84 Point of Use Treatment Technologies (WATERSPOUTT), Polo-López et al. (2019a)  
85 investigated various enhancement technologies that may cost-effectively allow for larger  
86 volumes of water to be treated using SODIS. Results from the study indicated that the use of  
87 a static batch reactor system employing U type solar mirrors allowed for the effective treatment  
88 of a larger volume (68% more) of water as compared to the compound parabolic collector  
89 (CPC)-type solar mirrors under the same solar exposure conditions (Polo-López et al. 2019a).  
90 In a follow-up study, the same research group designed two large-scale solar reactor  
91 prototypes (static batch systems with 88 L and 140 L treatment volumes, respectively), where  
92 multiple poly(methyl methacrylate) (PMMA) reactor tubes were positioned in the centre of U-  
93 type solar mirrors (Polo-López et al. 2019b). Preliminary assessment of the solar reactor  
94 prototypes, using spiked synthetic rainwater samples and culture-based analysis, indicated  
95 that a  $\geq 6$  log removal efficiency was obtained for *Escherichia coli* (*E. coli*) and *Salmonella*  
96 *enteritidis* after 1.5 hour natural sunlight exposure, while a 2 hour sunlight exposure was  
97 required to achieve the same log reduction for *Enterococcus faecalis* and *Pseudomonas*  
98 *aeruginosa* (*P. aeruginosa*).

99 The primary aim of the current study was to assess the efficiency of the two newly  
100 designed large-scale solar reactor prototypes (Polo-López et al. 2019b) for the treatment of

101 RHRW on-site in a local informal settlement (140 L Prototype I) and a rural farming community  
102 (88 L Prototype II). The chemical quality of the RHRW before and after solar reactor treatment  
103 was routinely assessed by monitoring various physico-chemical parameters (e.g. temperature,  
104 pH, and turbidity), anions and cations. Additionally, the removal of traditional indicator  
105 organisms (*E. coli*, total and faecal coliforms, enterococci and heterotrophic bacteria) and  
106 selected opportunistic pathogens (*Klebsiella* spp., *Pseudomonas* spp. and *Salmonella* spp.),  
107 was assessed using culture-based analysis. Ethidium monoazide bromide quantitative  
108 polymerase chain reaction (EMA-qPCR) assays were also used to monitor the reduction  
109 efficiency of indicator organisms (*E. coli* and enterococci) and opportunistic pathogens  
110 (*Klebsiella* spp., *Legionella* spp., *Pseudomonas* spp., and *Salmonella* spp.), while propidium  
111 monoazide (PMA) qPCR assays were used to monitor *Cryptosporidium* oocyst reductions. A  
112 water safety plan (WSP) outlining guidelines for the use of rainwater harvesting combined with  
113 solar reactor treatment was also implemented.

## 114 **2. Materials and methods**

### 115 **2.1 Description of large-scale solar reactor prototypes and sampling sites**

116 Two large-scale solar reactor prototypes were designed and constructed as part of Work  
117 Package 1 (WP1) by the WATERSPOUTT research consortium as part of a EU Horizon 2020  
118 project under grant agreement no. 688928 for implementation in South Africa and Uganda.  
119 Detailed information on the design and working mechanisms of the systems are outlined in  
120 [Polo-López et al. \(2019b\)](#), with the current study focussing on the application of these systems  
121 in field trials in South Africa. The Prototype I solar reactor (140 L treatment volume) was  
122 installed in Enkanini informal settlement (Site 1; GPS coordinates: 33°55'28.1"S 18°50'35.8"E)  
123 during July 2018 and consisted of three PMMA reactor tubes (200 mm diameter) that were  
124 positioned in the centre of a U-type solar mirror (constructed from anodized aluminium). The  
125 reactor tubes were positioned at a 34° angle (equal to the local **latitude**) and were inter-  
126 connected by UV-A transparent PMMA tubing (Fig. 1A). The Prototype II solar reactor (88 L

127 treatment volume) was installed next to a local church building in the Skoolplaas farming  
128 community (Site 2; GPS coordinates: 33°56'38.5"S 18°46'26.3"E) during July 2018 and  
129 consisted of the same materials and design as Prototype I, with the exception that eight PMMA  
130 tubes (100 mm diameter) were used in the system (Fig. 1B). Additionally, as space was  
131 available between the gutter system and the rainwater harvesting (RWH) tank at site 2, a first-  
132 flush (FF) diverter (Superhead® rainwater filter) was installed to redirect the initial roof run-off  
133 during a rain event (Fig. 1B). A detailed description of the sampling sites and system  
134 installation is outlined in Appendix A.

## 135 **2.2 Sample collection**

136 For the microbial and chemical analysis of the water produced by the solar reactor prototypes  
137 (Fig. 1), an untreated 10 L sample was collected directly from the RWH tank at each site  
138 [hereafter referred to as Tank 1 (Site 1) and Tank 2-FF (Site 2)]. The respective solar reactor  
139 prototypes were filled with tank water from the RWH tanks and exposed to direct sunlight for  
140 6 hours (sampling sessions 1 to 8) or 8 hours (sampling sessions 9 to 18). Following the solar  
141 exposure, 10 L of each treated sample was collected directly from the solar reactor **prototypes**  
142 [hereafter referred to as Prototype I (Site 1) and Prototype II (Site 2)]. Based on the availability  
143 of rainwater in the RWH tanks, 15 sampling sessions were conducted at site 1 ( $n = 30$ ; August  
144 2018 to March 2019), while 18 sampling sessions were conducted at site 2 ( $n = 36$ ; August  
145 2018 to April 2019). For ease of presentation, sampling sessions 1 to 18 are designated as  
146 #1 (sampling session 1), #2 (sampling session 2), etc., throughout the manuscript.

147 The temperature, pH and total dissolved solids present in all water samples were  
148 measured using a hand-held Milwaukee Instruments MI806 meter (Spraytech, South Africa),  
149 while the dissolved oxygen was measured using a Milwaukee Instruments M600 meter  
150 (Spraytech, South Africa). Rainfall and daily ambient temperature data for the study period  
151 was obtained from the South African Weather Services, while solar irradiance data [mean  
152 ambient UV-A and UV-B radiation] was obtained from the Stellenbosch Weather Services  
153 [Stellenbosch University, Faculty of Engineering ([http:// weather.sun.ac.za/](http://weather.sun.ac.za/))].

154 **2.3 Chemical analysis**

155 The chemical quality of the untreated and solar reactor treated tank water samples was  
156 determined by monitoring cation and anion concentrations and turbidity as described by  
157 Strauss et al. (2018). All samples ( $n = 66$ ) were monitored for cations, while representative  
158 samples ( $n = 22$ ; #1, #7, #10, #12, #15 and #18) were monitored for anions and turbidity.

159 **2.4 Culturing of indicator organisms and opportunistic pathogens**

160 The microbial quality of the tank water samples collected from sites 1 and 2 were monitored  
161 before (untreated) and after solar reactor treatment using various culture-based analyses.  
162 *Escherichia coli* and total coliforms were enumerated simultaneously using membrane  
163 filtration as described by Dobrowsky et al. (2015), while enterococci, faecal coliforms and the  
164 heterotrophic plate count/bacteria (HPC) were enumerated as outlined in Strauss et al. (2016),  
165 with a minor modification; Luria Bertani (LB) agar (Biolab, Merck, South Africa) replaced  
166 Reasoner's 2A agar (Oxoid, Hampshire, England) for the enumeration of HPC. For the treated  
167 samples (Prototypes I and II) where the HPC were reduced to below the detection limit [BDL;  
168  $< 1$  colony forming units (CFU)/1 mL], the potential regrowth of bacteria was monitored. Briefly,  
169 20 mL of each treated sample was stored in a sterile McCartney bottle at room temperature  
170 and 100  $\mu$ L of the treated water was spread plated onto LB agar (Biolab, Merck) every 24  
171 hours for a period of 2 days. The plates were then incubated at 37 °C. Additionally, *Klebsiella*  
172 spp., *Pseudomonas* spp. and *Salmonella* spp. were enumerated as outlined in Clements et  
173 al. (2019), while coliphages were enumerated as outlined by Baker et al. (2003) using *E. coli*  
174 ATCC 13706 as the target bacterial host. All culture-based analyses were performed in  
175 duplicate.

176 **2.5 Tank water concentration, viability treatment and DNA extraction**

177 The concentration of 1 L (Site 1) and 2 L (Site 2) samples, EMA treatment and subsequent  
178 DNA extractions were performed for each of the samples collected before and after solar

179 reactor treatment as outlined in Reyneke et al. (2016). For the molecular quantification of  
180 *Cryptosporidium* spp. within the collected samples, the same methodology was repeated with  
181 the exception that a PMA treatment as described by Alonso et al. (2014) was followed.

## 182 **2.6 Molecular-based enumeration of indicator organisms and opportunistic pathogens**

183 Quantitative PCR was performed in order to quantify *E. coli*, enterococci, *Klebsiella* spp.,  
184 *Legionella* spp., *Pseudomonas* spp. and *Salmonella* spp. in all of the collected tank water  
185 samples, while *Cryptosporidium* oocysts were quantified in the samples collected from #9 to  
186 #15 and #9 to #18 for sites 1 and 2, respectively. All qPCR assays were conducted using a  
187 LightCycler® 96 (Roche Diagnostics, Risch-Rotkreuz, Switzerland) instrument in combination  
188 with the FastStart Essential DNA Green Master Mix (Roche Diagnostics) as outlined in  
189 Reyneke et al. (2017), with the primer pairs and cycling parameters presented in Table A1.  
190 Standard curves for the respective qPCR assays were generated using the methodology  
191 outlined in Reyneke et al. (2017), while the qPCR performance characteristics of the various  
192 assays were analysed using the Roche LightCycler® 96 Software Version 1.1. Furthermore,  
193 to compensate for the different sample volumes used per site for rainwater concentration [1 L  
194 (Site 1) and 2 L (Site 2)] the gene copies detected in the samples utilising the qPCR assays  
195 were converted to gene copies per 100 mL of the original tank water sample as outlined by  
196 Waso et al. (2018). The gene copy numbers (gene copies/100 mL) were then converted to  
197 cell equivalents (cells or oocysts/100 mL) by utilising the number of copies of the target gene  
198 present within the target host (Table A1). All final concentrations for qPCR analyses are thus  
199 presented as equivalent cells or oocysts/100 mL original tank water sample.

## 200 **2.7 Maintenance of prototype reactors and water safety plan**

201 Following the system installations, workshops were conducted within the respective  
202 communities to outline the principle of rainwater harvesting, the working mechanism and  
203 operational maintenance of the solar reactors. Information on the domestic activities (i.e.  
204 laundry, cleaning, washing, etc.) the treated rainwater could be used for was also provided



205 (Fig. A3). Exemption from ethical clearance was obtained from the Research Ethics  
206 Committee (Humanities) Stellenbosch University (Ethics Reference no.: SU-HSD-004624), as  
207 the participating households would not be using the treated water for drinking purposes.

208 As outlined by the WHO (2004), the most efficient way of consistently ensuring the  
209 safety of a drinking water supply is through the utilisation of a WSP (Appendix B), which may  
210 be defined as a risk assessment and management approach that monitors the entire water  
211 supply process (e.g. collection of RHRW to utilisation of treated tank water by the consumer).  
212 The first step in the development of the WSP was to identify all potential hazards/hazardous  
213 events that may influence the quality of rainwater during the harvesting process, storage and  
214 treatment process (Appendix B), using published literature and personal observations at the  
215 respective study sites, during the study period. Additionally, various maintenance and  
216 remedial actions were identified to prevent certain water safety hazards (e.g. prevent organic  
217 debris from entering the storage tank) or to implement after a hazardous event occurred (e.g.  
218 control measure failed and organic debris washed into the storage tank) (Appendix B).  
219 Following the identification of the potential hazards, a risk assessment matrix (Appendix C)  
220 was compiled that would enable the risk characterisation associated with each  
221 hazard/hazardous event and enable the assessment of the various control measures (e.g.  
222 maintenance strategies, use of a first-flush diverter system etc.) in eliminating the identified  
223 water safety hazards.

## 224 **2.8 Statistical analysis**

225 Statistical analyses were conducted utilising either RStudio (version 1.0.153) or Microsoft  
226 Excel® Ver. 15.31. Overall differences in sample composition between site 1 and site 2 and  
227 the untreated (Tank 1 and Tank 2) and solar reactor treated (Prototype I and II) tank water  
228 samples was determined by evaluating all measured physico-chemical, chemical and  
229 microbial parameters using the parametric paired *t*-test (significant when  $p < 0.05$ ). Principle  
230 component analysis (PCA) was then used to visualise the correlations between the measured

231 cations at both sites and identify which cations primarily influenced the sample composition at  
232 each site.

### 233 **3. Results and Discussion**

#### 234 **3.1 Physico-chemical properties and chemical analysis of the collected tank water** 235 **samples**

236 The mean ambient UV-A radiation at both sampling sites ranged from 7.16 W/m<sup>2</sup> (12/09/2018)  
237 to 31.29 W/m<sup>2</sup> (14/01/2019), while the mean ambient UV-B radiation ranged from 1.33 W/m<sup>2</sup>  
238 (12/09/2018) to 4.63 W/m<sup>2</sup> (14/01/2019) (Table A2). The untreated tank water temperature at  
239 site 1 (Tank 1) ranged from 9.0 °C (02/08/2018 and 15/08/2018) to 24.0 °C (28/01/2019), with  
240 a mean temperature of 16.3 °C recorded for all sampling days, while the tank water  
241 temperature in the samples collected from the Prototype I solar reactor ranged from 15.5 °C  
242 (12/09/2018) to 45.0 °C (28/01/2019) (mean 28.9 °C). Similarly, the untreated tank water  
243 temperature at site 2 (Tank 2-FF) ranged from 10.0 °C (15/08/2018) to 26.0 °C (25/10/2018)  
244 (mean 18.1 °C), while the tank water temperature in the samples collected from the Prototype  
245 II solar reactor ranged from 18.0 °C (12/09/2018) to 46.5 °C (28/01/2019) (mean 32.6 °C).

246 All measured physico-chemical parameters (pH, turbidity, electrical conductivity, total  
247 dissolved solids and dissolved oxygen) in the collected untreated and prototype treated  
248 rainwater samples adhered to the drinking water guideline limits of the South African  
249 Department of Water Affairs and Forestry (DWAF) (DWAF, 1996), South African National  
250 Standards (SANS) 241 [South African Bureau of Standards (SABS), 2005], Australian  
251 Drinking Water Guidelines (ADWG) (NHMRC and NRMCC, 2011) and WHO (2011), with no  
252 significant difference ( $p > 0.05$ ) observed for the data collected for the untreated and treated  
253 (Tank 1 and Prototype I; Tank 2-FF and Prototype II) tank water samples or between sites 1  
254 and 2 (Tank 1 and 2-FF) (Table A3).

255 Results for the chemical analyses of the untreated (Tank 1 and Tank 2-FF) and treated  
256 (Prototype I and Prototype II) tank water samples collected from sites 1 and 2, indicated that

257 all anions and cations (Table A3) were within the respective drinking water guideline limits  
258 [DWAF, 1996; SANS 241 (SABS, 2005); ADWG (NHMRC and NRMCC, 2011); WHO, 2011],  
259 with the exception of the mean zinc (Zn) concentration recorded in the samples collected from  
260 site 1 [Tank 1 (mean of 3044 µg/L) and Prototype I (mean of 3061 µg/L)]; which exceeded  
261 (albeit not significantly) the DWAF (1996) and ADWG (NHMRC and NRMCC, 2011) limit of  
262 3000 µg/L. However, these samples were within the 5000 µg/L SANS 241 (SABS, 2005) limit.  
263 The increased Zn concentrations recorded at site 1 (Tank 1 and Prototype I), in comparison  
264 to site 2 (Tank 2-FF and Prototype II), may primarily be attributed to the metal sheeting (e.g.  
265 Zn sheeting) roofing material used to construct the catchment system, as the leaching of  
266 metals from metal roofing materials (corrosion during rain events and continuous exposure to  
267 sunlight) have been reported to be a major contributor of metal ions in rainwater (Chang et al.  
268 2004; Reyneke et al. 2018). It should be noted, that while the catchment system at site 2 was  
269 also constructed from Zn sheeting roofing material, the entire surface of the catchment system  
270 was painted with a weather resistant roof paint (personal communication) which may have  
271 limited the leaching of metal ions into the rainwater. Additionally, the first-flush diverter  
272 connected to the rainwater tank at site 2 (Tank 2-FF) may have improved the physico-chemical  
273 quality of the tank water samples. First-flush diverter systems act as a pre-treatment barrier  
274 by redirecting the initial roof run-off water (at the start of a rain event), which is thought to  
275 contain the highest concentration of pollutants (Sánchez et al. 2015). Gikas and Tsihrintzis  
276 (2012) compared the quality of RHRW collected in the flush pipe of first-flush diverter systems,  
277 with the RHRW entering the collection tanks (RWH tanks) and reported that all measured  
278 mean anion and cation concentrations were higher in the collected first-flush samples. The  
279 authors concluded that the diversion of the first-flush roof run-off away from the collection  
280 tanks may improve the physico-chemical quality of the RHRW.

281 As no significant difference was obtained when comparing the anion and cation  
282 concentrations (Table A3) recorded in the untreated tank water samples to the treated tank  
283 water samples (Tank 1 vs Prototype I, Tank 2-FF vs Prototype II) and the tank water samples  
284 from each site clustered together (Fig. 2), it was concluded that the solar reactor prototypes

285 (system components and the treatment mechanism) did not influence the chemical quality of  
286 the tank water samples.

## 287 **3.2 Removal efficiency of indicator bacteria and opportunistic pathogens**

### 288 **3.2.1 Culture-based analysis**

289 For the untreated tank water samples collected from site 1 (Tank 1;  $n = 15$ ), the *E. coli*, faecal  
290 coliform, total coliform, enterococci and HPC concentrations exceeded the respective drinking  
291 water guideline limits in 67%, 73%, 100%, 20% and 100% of the samples, respectively (Table  
292 1). Analysis of the corresponding treated samples (Prototype I;  $n = 15$ ) indicated that the  
293 *E. coli* ( $> 0.78$  log reduction), enterococci ( $> 3.48$  log reduction) and faecal coliform ( $> 4.08$   
294 log reduction) concentrations were reduced to BDL ( $< 1$  CFU/100 mL) in all the collected  
295 samples. Total coliforms were reduced to BDL in 63% of the treated samples collected  
296 following a 6 hour solar exposure (# 1-8) ( $> 3.94$  log reduction), with a mean of 55 CFU/100 mL  
297 detected in the samples (37%) where total coliform counts above the standard were detected.  
298 An increase in solar exposure to 8 hours (# 9-15) resulted in an increased treatment efficiency,  
299 as total coliforms were reduced to within the 5 CFU/100 mL DWAF (1996) and  
300 10 CFU/100 mL SANS 241 (SABS, 2005) guideline limits in 100% of the treated samples (4.66  
301 log reduction). For the HPC analysis, 38% of the treated samples were reduced to within the  
302 drinking water guideline limit of  $1.0 \times 10^4$  CFU/100 mL (1.71 log reduction) after a 6 hour solar  
303 exposure [mean of  $2.4 \times 10^4$  CFU/100 mL detected in the remaining 63% samples (1.21 log  
304 reduction)], while 57% of the treated samples were reduced to within the guideline limit (2.08  
305 log reduction) after an 8 hour solar exposure [mean of  $2.7 \times 10^4$  CFU/100 mL detected in the  
306 remaining 43% of samples (1.01 log reduction)] (Fig. A6).

307 For the untreated tank water samples collected from site 2 (Tank 2-FF;  $n = 18$ ), the  
308 *E. coli*, faecal coliform, total coliform, enterococci and HPC concentrations exceeded the  
309 respective drinking water guideline limits in 56%, 22%, 100%, 28% and 100% of the samples,  
310 respectively (Table 1). Analysis of the corresponding treated samples (Prototype II;  $n = 18$ )

311 indicated that the *E. coli* (> 0.48 log reduction), enterococci (> 3.34 log reduction) and faecal  
312 coliform (> 3.04 log reduction) concentrations were reduced to BDL (< 1 CFU/100 mL) in all  
313 collected samples, while total coliforms were reduced to within the 5 CFU/100 mL DWAF  
314 (1996) and 10 CFU/100 mL SANS 241 (SABS, 2005) guideline limits (3.85 log reduction).  
315 Heterotrophic bacteria were then reduced to within the  $1.0 \times 10^4$  CFU/100 mL DWAF (1996)  
316 drinking water guideline limit in 88% of the treated samples (mean of  $4.6 \times 10^3$  CFU/100 mL  
317 recorded) after a 6 hour solar exposure (# 1-8) (2.11 log reduction), with a mean of  
318  $1.8 \times 10^4$  CFU/100 mL detected in the samples (12%) where HPC concentrations above the  
319 standard were detected. In comparison, 100% of the treated samples were reduced to within  
320 the  $1.0 \times 10^4$  CFU/100 mL drinking water guideline limit after an 8 hour solar exposure (# 9-  
321 18) ( $\geq 2.02$  log reduction; Fig. A6).

322 *Klebsiella* spp. were detected in 100% (mean concentration of  $1.9 \times 10^4$  CFU/100 mL)  
323 and *Salmonella* spp. in 60% (mean concentration of  $6.3 \times 10^3$  CFU/100 mL) of the untreated  
324 rainwater samples collected from site 1 (Tank 1); however, both organisms were reduced to  
325 BDL (> 4.28 and > 3.8 log reduction, respectively) following treatment using the Prototype I  
326 solar reactor (Table 1). *Klebsiella* spp. were also detected in 17% (mean concentration of  
327  $8.0 \times 10^2$  CFU/100 mL) and *Salmonella* spp. in 6% (mean concentration of  
328  $1.0 \times 10^3$  CFU/100 mL) of the untreated rainwater samples collected from site 2 (Tank 2-FF),  
329 with both organisms reduced to BDL (> 2.9 and > 3 log reduction, respectively) following  
330 treatment using the Prototype II solar reactor (Table 1). *Pseudomonas* spp. and coliphages  
331 were not detected in any of the rainwater samples collected from sites 1 and 2.

332 Although numerous studies have investigated the use of SODIS to treat contaminated  
333 water, varying degrees of treatment efficiency (0.46 to > 6 log reductions in bacteria) have  
334 been reported depending on experimental design (McGuigan et al. 2012; Hamilton et al.  
335 2019). However, a limitation of SODIS which has consistently been highlighted by these  
336 investigators is the small treatment volume (2 to 5 L). Ubomba-Jaswa et al. (2010) investigated  
337 the use of a 25 L SODIS reactor (methacrylate tube) situated inside a CPC and reported on  
338 the complete inactivation of *E. coli*, even during unfavourable weather conditions (cloudy with

339 low solar intensity). Polo- López et al. (2019a) then expanded on this research and  
340 investigated cost-effective SODIS enhancement strategies that would enable the treatment of  
341 larger volumes of water (32 L and 54 L), with the results obtained leading to the design of the  
342 large-scale solar reactor prototypes (Prototype I and II) assessed in the current study. The  
343 treatment efficiency of the Prototype I and II solar reactors was also assessed by Polo-López  
344 et al. (2019b) under controlled conditions, by spiking synthetic rainwater with laboratory strains  
345 of *E. coli*, enterococci, *Salmonella* and *Pseudomonas* ( $10^5 - 10^6$  CFU/mL bacterial cells) using  
346 a 6 hour solar exposure treatment time. A  $\geq 6$  log reduction of all the test bacteria was  
347 obtained, with the system classified as “highly protective ( $\geq 4$  log reduction)” against bacteria  
348 according to the WHO (2016) household water treatment technology performance criteria. In  
349 comparison, results from the current study, for both solar reactor prototypes, during a 6 hour  
350 solar exposure treatment, indicated that  $\geq 2.54$  log reduction was obtained when monitoring  
351 the removal of enterococci, faecal and total coliforms, while mean log reductions of  $\geq 1.21$  log  
352 were obtained for the removal of HPC. Based on these results, the 6 hour solar exposure  
353 treatment with the prototypes in field trials failed to meet the  $\geq 2$  log removal required for a  
354 “protective” classification against bacteria. The Polo-López et al. (2019b) study was however,  
355 conducted in a hot arid climate (Tabernas Dessert, Almería, Spain) with a mean UV radiation  
356 of  $28.31 \text{ W/m}^2/\text{h}$  recorded during the 6 hour treatment trials, while the field trials of the systems  
357 in the current study were conducted in a moderate Mediterranean climate (Stellenbosch,  
358 Western Cape, South Africa), where a mean UV radiation of  $20.82 \text{ W/m}^2/\text{h}$  was recorded  
359 during the 6 hour treatment trials (Table A2).

360 The treatment time in the current study was subsequently increased to 8 hours (Site  
361 1: #9-15; Site 2: #9-18) in order to increase the overall UV dose (mean UV radiation of  
362  $24.72 \text{ W/m}^2/\text{h}$  was recorded from #9-18). For both prototypes a  $\geq 3.44$  log reduction was  
363 subsequently obtained when monitoring the removal of enterococci, faecal and total coliforms,  
364 while the mean log reductions for the removal of HPC increased to  $\geq 2.02$  log. Based on the  
365 observed treatment efficiencies obtained using the Prototype I and II solar reactors in the  
366 current study (8 hour treatment), the prototypes may be classified as “protective ( $\geq 2$  log

367 reduction)", for the removal of bacteria in the tank water (WHO, 2016). More importantly,  
368 culture-based analysis indicated that both treatment systems were able to produce water that  
369 adhered to the microbial parameters as stipulated in the respective drinking water guidelines  
370 [DWAF, 1996; SANS 241 (SABS, 2005); ADWG (NHMRC and NRMCC, 2011); WHO, 2011],  
371 with lower indicator organism counts recorded in the tank water samples collected from site 2,  
372 where the first-flush diverter system was installed. The treated water collected from the large-  
373 scale solar reactor prototypes could however, only be stored for a maximum of 24 hours, as  
374 microbial re-growth occurred after this point.

### 375 **3.2.2 Molecular-based analysis**

376 The performance characteristics of the respective qPCR assays are provided in Table A4.  
377 Results obtained using EMA-qPCR indicated that an overall mean decrease of 83.76% (0.79  
378 log reduction) in intact *E. coli* cells was recorded after treatment using Prototype I, while an  
379 overall mean decrease of 82.76% (0.76 log reduction) was recorded after treatment for  
380 Prototype II (Fig. 3). Similarly, intact enterococci cells decreased by a mean of 91.68% (1.08  
381 log reduction) after treatment using Prototype I, while an 84.89% (0.82 log reduction) mean  
382 decrease was recorded after treatment using Prototype II (Fig. 3). In comparison,  
383 quantification of intact *Klebsiella* cells indicated that this genus was more resistant to the solar  
384 reactor treatment as mean decreases of 62.44% (0.43 log reduction) and 60.42% (0.40 log  
385 reduction) were recorded after treatment using Prototype I and II, respectively (Fig. 3).  
386 Similarly, intact *Legionella* cells decreased by 68.61% (0.50 log reduction) after treatment  
387 using Prototype I and by 63.77% (0.44 log reduction) after treatment using Prototype II (Fig.  
388 3). Overall mean decreases in intact *Pseudomonas* cells of 79.09% (0.68 log reduction) and  
389 87.50% (0.90 log reduction) were recorded after treatment using Prototype I and II,  
390 respectively, while *Salmonella* cells decreased by 78.36% (0.66 log reduction) after treatment  
391 using Prototype I and 67.82% (0.49 log reduction) after treatment with Prototype II (Fig. 3).  
392 Lastly, PMA-qPCR analysis indicated that *Cryptosporidium* oocysts decreased by 57.14%

393 (0.62 log reduction) after treatment using Prototype I, while a mean decrease of 73.81% (0.58  
394 log reduction) was recorded after treatment using Prototype II (Fig. 3).

395 Overall, the EMA-qPCR and PMA-qPCR analysis indicated that the Prototype I and II  
396 solar reactors reduced the opportunistic pathogens by 74.43%. This discrepancy in the  
397 observed treatment efficiency in comparison to the results obtained using culture-based  
398 analysis, may be attributed to EMA-qPCR and PMA-qPCR detecting viable but non culturable  
399 (VBNC) cells within the water samples (Fittipaldi et al. 2012; Mansi et al. 2014). It has been  
400 reported that certain opportunistic pathogens (e.g. *Legionella pneumophila* and  
401 *P. aeruginosa*) can enter a VBNC state in which they are not detectable using standard  
402 culture-based analysis but are still viable and retain their virulence (Mansi et al. 2014).  
403 Moreover, these VBNC microorganisms may regain their ability to be cultured under  
404 favourable conditions, which corresponds to the observed bacterial re-growth observed after  
405 24 hours (culture-based analysis). Strauss et al. (2019) then applied Illumina next-generation  
406 sequencing coupled with EMA viability treatment to identify the primary pathogenic or  
407 opportunistic pathogenic genera, capable of surviving SODIS-CPC treatment in a 10.6 L CPC-  
408 reactor (Strauss et al. 2019). Results from the study indicated that intact and potentially viable  
409 bacterial cells belonging to 11 different bacterial genera (e.g. *Acinetobacter*, *Campylobacter*,  
410 *Legionella*, *Mycobacterium* and *Pseudomonas* amongst others) were detected in the SODIS-  
411 CPC treated tank water. Monitoring for the presence of VBNC microorganisms following water  
412 treatment is thus essential as these VBNC bacteria still pose a health risk as they are  
413 potentially infectious (Mansi et al. 2014).

414 While the survival of the *Cryptosporidium* oocysts after SODIS treatment using the  
415 solar reactor prototypes, may be attributed to the resilient nature of the oocyst wall (Hamilton  
416 et al. 2018), the ability of the opportunistic pathogenic bacteria (*Pseudomonas* spp.,  
417 *Salmonella* spp., *Legionella* spp. and *Klebsiella* spp.) to survive large-scale solar-based  
418 disinfection strategies has been attributed to their ability to initiate various stress-response  
419 mechanisms and switch to a more tolerant phenotype upon exposure to environmental  
420 stressors, such as temperature and UV exposure (Jones, 1997; Fux et al. 2005). These stress-



421 responses may include the production of heat shock proteins and the initiation of DNA repair  
422 mechanisms, amongst others (Fields et al. 2002; Breidenstein et al. 2011). For example,  
423 Srivastava et al. (2008) indicated that the overexpression of the sigma factor *algT*, protects  
424 *Pseudomonas* spp. from heat stress and allows these organisms to persist during  
425 unfavourable conditions, while DNA repair mechanisms may be initiated in response to UV-  
426 induced DNA damage, through the activation of the SOS-regulon (upregulation of *recA* and  
427 *lexA*) or the photolyase enzyme (Zenoff et al. 2006). Similarly, Bojer et al. (2010) attributed  
428 the heat resistance of *K. pneumoniae* to the *clpK* genetic marker, which has been shown to  
429 correlate positively with thermotolerant phenotypes observed among clinical *Klebsiella*  
430 isolates. Microorganisms have also been reported to produce pigments or structures that may  
431 enable their survival under unfavourable conditions, as has been reported for *P. aeruginosa*  
432 where the production of pyocyanin has been hypothesised to protect *P. aeruginosa* from  
433 oxidative stress (inactivation mechanism of SODIS) (Hendiani et al. 2019). It is thus evident  
434 that microorganisms may employ numerous strategies to survive disinfection treatment and  
435 that additional treatment barriers may be required to reduce the survival of these target  
436 pathogens within water treatment systems. These strategies may include the addition of a  
437 cost-effective filtration system as a pre-treatment strategy to reduce microbial load entering  
438 the large-scale solar reactor prototypes (Hamilton et al. 2019).

### 439 **3.3 Water safety plan and operational sustainability of the systems**

440 As numerous factors may influence the quality of RHRW during the harvesting and/or  
441 treatment process, a WSP (Appendix B) for the utilisation of rainwater harvesting in  
442 combination with the large-scale solar reactor prototypes was developed. As the WSP was  
443 developed concurrently with the monitoring of the large-scale solar reactor prototypes during  
444 the field trials, the effectiveness of the various control measures was assessed by comparing  
445 site 1 with site 2, as these sites were located in two distinct settings that could be influenced  
446 by different anthropogenic activities and potential pollution sources as outlined in Appendix A.

447 The application of the WSP to characterise the risk associated with RHRW collected  
448 at sites 1 and 2, indicated that the external hazards at site 1 (informal settlement) posed a  
449 greater risk of contamination. The increased risk was primarily attributed to the influence of  
450 potential pollution sources present near the catchment system (e.g. garbage disposal site,  
451 surface run-off), tree branches obstructing a section of the conveyance system, organic debris  
452 (e.g. dust/soil dispersed from the dirt pathway, leaves from the tree) within the conveyance  
453 system and corrosion of the metal sheeting catchment system. Correspondingly, chemical and  
454 microbial analysis of the untreated tank water samples collected from sites 1 and 2 revealed  
455 that the untreated tank water collected from site 1 had higher levels of chemical contaminants  
456 (e.g. cations) and microbial contaminants in comparison to site 2. For example, the  
457 concentration of HPC was 0.72 log [ $3.50 \times 10^5$  CFU/100 mL (Tank 1) vs  $6.90 \times 10^4$   
458 CFU/100 mL (Tank 2-FF)] greater in the untreated tank water samples from site 1 (Tank 1), in  
459 comparison to site 2 (Tank 2-FF).

460 The improved tank water quality at site 2 may also be attributed to the efficiency of the  
461 implemented control measures at this site. The catchment surface at site 2 was painted with  
462 a weather resistant roof paint that may have reduced the leaching of metal contaminants into  
463 the collected tank water. Additionally, due to space availability a first-flush diverter was  
464 connected between the catchment system and Tank 2-FF, which served as a control measure  
465 to reduce the introduction of organic debris into the collection tank. However, the efficiency of  
466 a first-flush diverter is dependent on the maintenance of the system, which entailed  
467 cleaning/emptying the first-flush diverter after each rain event. The quality of RHRW collected  
468 from site 1 may then be improved by removing the obstructing tree branches (source of  
469 organic debris), implementing a regular gutter cleaning regime, installing a gutter screen at  
470 the inlet of the RWH tank (due to space limitation a first-flush diverter could not be connected  
471 to the current catchment system) and replacing the corroded metal sheeting on the catchment  
472 system or painting the catchment system with a weather resistant roof paint.

473 As previously indicated, workshops were conducted with participating households  
474 within the respective communities to outline the operational maintenance of the large-scale

475 solar reactor prototypes and rainwater harvesting systems (Fig. A3). Subsequent monitoring  
476 of the operational sustainability of the solar reactor prototypes at both sites indicated that  
477 system maintenance was limited to cleaning the surface of the PMMA reactor tubes (prevent  
478 dust accumulation that will influence UV transmittance), with no system components needing  
479 replacement during the study period. The robustness of system components therefore also  
480 needs to be taken into consideration when designing water treatment systems for use in rural  
481 areas and informal settlements, where replacement components may not be readily available.  
482 During the study period, households who had access to the treated tank water (Prototype I  
483 and II) at sites 1 (13 households) and site 2 (5 households), primarily reported using the treated  
484 tank water for domestic activities such as cleaning of their homes, laundry and washing.

485 As noted by Mahmud et al. (2007), the aim of a WSP for small community water  
486 supplies should be to achieve an overall and sustained reduction in microbial  
487 contaminants/sanitary risks, rather than aim for the complete removal of microbial  
488 contaminants. The WSP outlined in the current study thus serves to reduce the contamination  
489 of RHRW by reducing “preventable contaminant entry” (e.g. organic debris and faecal matter  
490 containing an increased microbial load from washing into the storage tank) into the storage  
491 tank, whereafter treatment with the large-scale solar reactor prototypes may further reduce  
492 the microbial contaminants to within drinking water standards.

#### 493 **4. Conclusions**

494 The physico-chemical and chemical quality of the Tank 1 and 2-FF and Prototype I and II  
495 treated rainwater samples adhered to the respective drinking water guidelines, with an  
496 improvement in quality observed at site 2 where the first-flush diverter was installed. Lower  
497 indicator bacterial counts were also recorded in the tank water samples collected from site 2  
498 (Tank 2-FF and Prototype II) where the first-flush diverter was installed and fewer hazards  
499 were identified that may influence the tank water quality (WSP), in comparison to site 1 (Tank  
500 1 and Prototype I). The installation of a first-flush diverter system may thus serve as an  
501 inexpensive pre-treatment strategy that may improve the overall quality of RHRW, while the

502 establishment of a WSP may aid in identifying potential hazards/hazardous events that may  
503 influence water safety.

504 Although both reactor prototypes were able to significantly improve the microbial  
505 quality of the tank water after an 8 hour solar treatment, HPC exceeding the DWAF (1996)  
506 drinking water guideline limit were recorded in 43% of the Prototype I treated samples.

507 Nevertheless, a mean 1.01 log reduction in heterotrophic bacteria was recorded for these  
508 samples, which would decrease the health risk associated with using the treated rainwater (in  
509 comparison to the utilisation of untreated rainwater). Results from the EMA-qPCR and PMA-  
510 qPCR analysis indicated that *E. coli*, enterococci, *Klebsiella* spp., *Legionella* spp.,  
511 *Pseudomonas* spp., *Salmonella* spp. and *Cryptosporidium* oocysts were reduced by 74.43%  
512 in both reactor prototypes. While molecular analysis indicated that the target organisms in the  
513 treated rainwater samples were not reduced to below the detection limit, based on national  
514 and international drinking water guidelines, the large-scale solar reactor prototypes used in  
515 the current study may effectively treat rainwater to within drinking water standards. The 88 L  
516 and 140 L solar reactor prototype treatment systems may thus provide a viable water provision  
517 solution for the inhabitants of rural areas and urban informal settlements in sub-Saharan  
518 Africa.

#### 519 **Conflicts of interests**

520 The authors have no conflicts to declare.

#### 521 **Acknowledgements**

522 This project has received funding from the European Union's Horizon 2020 Research and  
523 Innovation Program under grant agreement no. 688928 (WATERSPOUTT H2020-Water-5c).

524 **References**

- 525 Alonso, J.L., Amorós, I., Guy, R.A., 2014. Quantification of viable *Giardia* cysts and  
526 *Cryptosporidium* oocysts in wastewater using propidium monoazide quantitative real-time  
527 PCR. *Parasitol. Res.* 113, 2671-2678. <https://doi.org/10.1007/s00436-014-3922-9>.
- 528 Baker, W.P., Leyva, K.J., Klotz, P., Wellington, R.R., 2003. Investigation of bacteriophage as  
529 indicators of fecal pollution in urban water samples. *Journal of the Arizona-Nevada Academy*  
530 *of Science.* 36, 1-4. <https://www.jstor.org/stable/40022384>.
- 531 Bojer, M.S., Struve, C., Ingmer, H., Hansen, D.S., Krogfelt, K.A., 2010. Heat resistance  
532 mediated by a new plasmid encoded Clp ATPase, ClpK, as a possible novel mechanism for  
533 nosocomial persistence of *Klebsiella pneumoniae*. *PLoS ONE.* 5, e15467.  
534 <https://doi.org/10.1371/journal.pone.0015467>.
- 535 Breidenstein, E.B.M., De La Fuente-Núñez, C., Hancock, R.E.W., 2011. *Pseudomonas*  
536 *aeruginosa*: all roads lead to resistance. *Trends Microbiol.* 19, 419-426.  
537 <https://doi.org/10.1016/j.tim.2011.04.005>.
- 538 Chang, M., McBroom, M.W., Beasley, R.S., 2004. Roofing as a source of non-point water  
539 pollution. *J. Environ. Manage.* 73, 307-315. <https://doi.org/10.1016/j.jenvman.2004.06.014>.
- 540 Clements, T.L., Reyneke, B., Strauss, A., Khan, W., 2019. Persistence of viable bacteria in  
541 solar pasteurised harvested rainwater. *Water Air Soil Poll.* 230, 130.  
542 <http://dx.doi.org/10.1007/s11270-019-4184-z>.
- 543 Department of Water Affairs and Forestry (DWAf)., 1996. *South African Water Quality*  
544 *Guidelines* 2<sup>nd</sup> ed. Volume 1: Domestic Water Use. Pretoria, South Africa: CSIR Environmental  
545 Services. ISBN 0-7988-5338-7.
- 546 Dobrowsky, P.H., Lombard, M., Cloete, W.J., Saayman, M., Cloete, T.E., Carstens, M., Khan,  
547 S., Khan, W., 2015. Efficiency of microfiltration systems for the removal of bacterial and viral

548 contaminants from surface and rainwater. *Water Air Soil Pollut.* 226, 33.  
549 <https://doi.org/10.1007/s11270-015-2317-6>.

550 Dos Santos, S., Adams, E.A., Neville, G., Wada, Y., De Sherbinin, A., Mullin Bernhardt, E.,  
551 Adamo, S.B., 2017. Urban growth and water access in sub-Saharan Africa: progress,  
552 challenges, and emerging research directions. *Sci. Total Environ.* 607-608, 497-508.  
553 <https://doi.org/10.1016/j.scitotenv.2017.06.157>.

554 Emenike, C.P., Tenebe, I.T., Omole, D.O., Ngene, B.U., Oniemayin, B.I., Maxwell, O., Onoka,  
555 B.I., 2017. Accessing safe drinking water in sub-Saharan Africa: Issues and challenges in  
556 South-West Nigeria. *Sustain. Cities Soc.* 30, 263-272.  
557 <https://doi.org/10.1016/j.scs.2017.01.005>.

558 Fields, B.S., Benson, R.F., Besser, R.E., 2002. *Legionella* and Legionnaires' disease: 25 years  
559 of investigation. *Clin. Microbiol. Rev.* 15, 506-526. [https://doi.org/10.1128/CMR.15.3.506-](https://doi.org/10.1128/CMR.15.3.506-526.2002)  
560 [526.2002](https://doi.org/10.1128/CMR.15.3.506-526.2002).

561 Fittipaldi, M., Nocker, A., Codony, F., 2012. Progress in understanding preferential detection  
562 of live cells using viability dyes in combination with DNA amplification. *J. Microbiol. Methods.*  
563 91, 276-289. <https://doi.org/10.1016/j.mimet.2012.08.007>.

564 Fux, C.A., Costerton, J.W., Stewart, P.S., Stoodley, P., 2005. Survival strategies of infectious  
565 biofilms. *Trends Microbiol.* 13, 34-40. <https://doi.org/10.1016/j.tim.2004.11.010>.

566 Gikas, G.D., Tsihrintzis, V.A., 2012. Assessment of water quality of first-flush roof runoff and  
567 harvested rainwater. *J. Hydrol.* 466-467, 115-126.  
568 <https://doi.org/10.1016/j.jhydrol.2012.08.020>.

569 Global Risks Report., 2019. *The Global Risks Report 2019 14th Edition*. Available:  
570 [http://www3.weforum.org/docs/WEF\\_Global\\_Risks\\_Report\\_2019.pdf](http://www3.weforum.org/docs/WEF_Global_Risks_Report_2019.pdf). [2019, February 10].

571 Gwenzi, W., Nyamadzawo, G., 2014. Hydrological impacts of urbanization and urban roof  
572 water harvesting in water-limited catchments: a review. Environ. Process. 1, 573-593.  
573 <https://doi.org/10.1007/s40710-014-0037-3>.

574 Hamilton, K.A., Waso, M., Reyneke, B., Saeidi, N., Levine, A., Lalancette, C., Besner, M-C.,  
575 Khan, W., Ahmed, W., 2018. *Cryptosporidium* and *Giardia* in wastewater and surface water  
576 environments. J Environ Qual. 47, 1006-1023. <https://doi.org/10.2134/jeq2018.04.0132>.

577 Hamilton, K.A., Reyneke, B., Waso, M., Clements, T.L., Ndlovu, T., Khan, W., Digiovanni, K.,  
578 Rakestraw, E., Montalto, F., Haas, C.N. Ahmed, W., 2019. A global review of the  
579 microbiological quality and potential health risks associated with roof-harvested rainwater  
580 tanks. Npj Clean Water. 2, 7. <https://doi.org/10.1038/s41545-019-0030-5>.

581 Hendiani, S., Pornour, M., Kashef, N., 2019. Quorum-sensing-regulated virulence factors in  
582 *Pseudomonas aeruginosa* are affected by sub-lethal photodynamic inactivation. Photodiagn.  
583 Photodyn. 26, 8-12. <https://doi.org/10.1016/j.pdpdt.2019.02.010>.

584 Jones, K., 1997. Strategies for survival. In: Coliforms and E. coli. Problem or solution? D. Kay  
585 & C. Fricker, Eds. Cambridge, UK: The Royal Society of Chemistry.

586 Mahmud, S.G., Abu Jafar Shamsuddin, S., Feroze Ahmed, M., Davison, A., Deere, D.,  
587 Howard, G., 2007. Development and implementation of water safety plans for small water  
588 supplies in Bangladesh: benefits and lessons learned. J. Water Health. 5, 585-597.  
589 <https://doi.org/10.2166/wh.2007.045>.

590 Mansi, A., Amori, I., Marchesi, I., Marcelloni, A.M., Proietto, A.R., Ferranti, G., Magini, V.,  
591 Valeriani, F., Borella, P., 2014. *Legionella* spp. survival after different disinfection procedures:  
592 Comparison between conventional culture, qPCR and EMA-qPCR. Microchem. J. 112, 65-69.  
593 <https://doi.org/10.1016/j.microc.2013.09.017>.

594 McGuigan, K.G., Conroy, R.M., Mosler, H., Du Preez, M., Ubomba-Jaswa, E., Fernandez-  
595 Ibañez, P., 2012. Solar water disinfection (SODIS): a review from bench-top to roof-top. J.  
596 Hazard. Mater. 235-236, 29-46. <https://doi.org/10.1016/j.jhazmat.2012.07.053>.

597 Nelson, K.L., Boehm, A.B., Davies-Colley, R.J., Dodd, M.C., Kohn, T., Linden, K.G., Liu, Y.,  
598 Maraccini, P.A., McNeill, K., Mitch, W.A., Nguyen, T.H., Parker, K.M., Rodriguez, R.A.,  
599 Sassoubre, L.M., Silverman, A.I., Wigginton, K.R., Zepp, R.G., 2018. Sunlight-mediated  
600 inactivation of health-relevant microorganisms in water: a review of mechanisms and  
601 modelling approaches. Environ. Sci.: Proc. Imp. 20, 1089.  
602 <https://doi.org/10.1039/c8em00047f>.

603 NHMRC and NRMCC (ADWG), 2011. *Australian drinking water guidelines Paper 6 National*  
604 *Water Quality Management Strategy*. National Health and Medical Research Council, National  
605 Resource Management Ministerial Council Commonwealth of Australia, Canberra.

606 Reyneke, B., Dobrowsky, P.H., Ndlovu, T., Khan, S., Khan, W., 2016. EMA-qPCR to monitor  
607 the efficiency of a closed-coupled solar pasteurization system in reducing *Legionella*  
608 contamination of roof-harvested rainwater. Sci. Total Environ. 553, 662-670.  
609 <https://doi.org/10.1016/j.scitotenv.2016.02.108>.

610 Reyneke, B., Ndlovu, T., Khan, S., Khan, W., 2017. Comparison of EMA-, PMA- and DNase  
611 qPCR for the determination of microbial cell viability. Appl. Microbiol. Biotechnol. 101, 7371-  
612 7383. <https://doi.org/10.1007/s00253-017-8471-6>.

613 Reyneke, B., Cloete, T.E., Khan, S., Khan, W., 2018. Rainwater harvesting solar  
614 pasteurization treatment systems for the provision of an alternative water source in peri-urban  
615 informal settlements. Environ. Sci: Water Res. Technol. 4, 291-302.  
616 <https://doi.org/10.1039/c7ew00392g>.



617 Sánchez, A.S., Cohim, E., Kalid, R.A., 2015. A review on physicochemical and microbiological  
618 contamination of roof-harvested rainwater in urban areas. *Sustainability of Water Quality and*  
619 *Ecology*. 6, 119-137. <https://doi.org/10.1016/j.swaqe.2015.04.002>.

620 South African Bureau of Standards (SABS). 2005. South African National Standards (SANS)  
621 241: In *Drinking water quality management guide for water services authorities*. 6<sup>th</sup> ed.  
622 Annexure 1. ISBN 0-626-17752-9.

623 Srivastava, S., Yadav, A., Seem, K., Mishra, S., Chaudhary, V., Nautiyal, C.S. 2008. Effect of  
624 high temperature on *Pseudomonas putida* NBRI0987 biofilm formation and expression of  
625 stress sigma factor RpoS. *Curr. Microbiol.* 56, 453-457. [https://doi.org/10.1007/s00284-008-](https://doi.org/10.1007/s00284-008-9105-0)  
626 [9105-0](https://doi.org/10.1007/s00284-008-9105-0).

627 Strauss A., Dobrowsky P.H., Ndlovu T., Reyneke B., Khan W., 2016. Comparative analysis of  
628 solar pasteurization versus solar disinfection for the treatment of harvested rainwater. *BMC*  
629 *Microbiol.* 16, 289. <https://doi.org/10.1186/s12866-016-0909-y>.

630 Strauss A., Reyneke B., Waso M., Khan W., 2018. Compound parabolic collector solar  
631 disinfection system for the treatment of harvested rainwater. *Environ. Sci.: Water Res.*  
632 *Technol.* 4, 976-991. <https://doi.org/10.1039/C8EW00152A>.

633 Strauss A., Reyneke B., Waso M., Ndlovu T., Brink C., Khan S., Khan W., 2019. EMA-  
634 amplicon-based taxonomic characterisation of the viable bacterial community present in  
635 untreated and SODIS treated roof-harvested rainwater. *Environ. Sci.: Water Res. Technol.* 5,  
636 91-101. <https://doi.org/10.1039/c8ew00613j>.

637 Ubomba-Jaswa, E., Fernández-Ibáñez, P., Navntoft, C., Polo-López, M.I., McGuigan, K.,  
638 2010. Investigating the microbial inactivation efficiency of a 25 L batch solar disinfection  
639 (SODIS) reactor enhanced with a compound parabolic collector (CPC) for household use. *J.*  
640 *Chem. Tech. Biotech.* 85, 1028-1037. <https://doi.org/10.1002/jctb.2398>.

641 Waso, M., Khan, S., Khan, W., 2018. Microbial source tracking markers associated with  
642 domestic rainwater harvesting systems: correlation to indicator organisms. *Environ. Res.* 161,  
643 446-455. <https://doi.org/10.1016/j.envres.2017.11.043>.

644 World Health Organisation (WHO)., 2004. *Guidelines for drinking-water quality*. Rev. 3<sup>rd</sup> ed.  
645 World Health Organisation. Geneva, Switzerland: WHO Press. ISBN: 92-4-154638-7.

646 World Health Organisation (WHO)., 2011. *Guidelines for drinking-water quality*. Rev. 4<sup>th</sup> ed.  
647 World Health Organisation. Geneva, Switzerland: WHO Press. ISBN: 978-92-4-154815-1.

648 World Health Organisation (WHO)., 2016. Results of round 1 of the WHO international scheme  
649 to evaluate household water treatment technologies. World Health Organisation.  
650 <https://apps.who.int/iris/handle/10665/204284>.

651 Zenoff, V.F., Siñeriz, F., Farías, M.E., 2006. Diverse responses to UV-B radiation and repair  
652 mechanisms of bacteria isolated from high-altitude aquatic environments. *Appl. Environ.*  
653 *Microbiol.* 72, 7857-7863. <https://doi.org/10.1128/AEM.01333-06>.

654

655

656

657

658

659

660

661

662 **Table 1** Frequency of detection and mean concentrations (CFU/100 mL) of indicator organisms  
 663 and target bacterial pathogens in the tank water samples collected from sites 1 and 2.

Organism	Site 1		Site 2	
	Tank 1 (n = 15)	Prototype I (n = 15)	Tank 2-FF (n = 18)	Prototype II (n = 18)
<i>E. coli</i>	67% (6)	BDL	51% (3)	BDL
Total coliforms	100% (1.5 × 10 <sup>4</sup> )	27% (42)	100% (1.0 × 10 <sup>3</sup> )	11% (2)
Enterococci	20% (3.0 × 10 <sup>3</sup> )	BDL	28% (2.2 × 10 <sup>3</sup> )	BDL
Faecal coliforms	73% (1.2 × 10 <sup>4</sup> )	BDL	22% (1.1 × 10 <sup>3</sup> )	BDL
Heterotrophic bacteria	100% (3.5 × 10 <sup>5</sup> )	50% (1.8 × 10 <sup>4</sup> )	100% (6.9 × 10 <sup>4</sup> )	86% (6.5 × 10 <sup>3</sup> )
<i>Klebsiella</i> spp.	100% (1.9 × 10 <sup>4</sup> )	BDL	17% (8.0 × 10 <sup>2</sup> )	BDL
<i>Pseudomonas</i> spp.	ND	ND	ND	ND
<i>Salmonella</i> spp.	60% (6.3 × 10 <sup>3</sup> )	BDL	6% (1.0 × 10 <sup>3</sup> )	BDL
Coliphages (PFU/mL)	ND	ND	ND	ND

664 BDL – below detection limit; ND – not detected; PFU – plaque forming units

665

666

667

668

669

670

671

672

673

674

675 **Figure Legends:**

676 **Fig. 1. (A)** The Prototype I (140 L) solar reactor installed at Site 1. **(B)** The Prototype II (88 L)  
677 solar reactor installed at Site 2. The red arrow indicates the first-flush diverter which was  
678 connected to Tank 2-FF.

679 **Fig. 2.** Principle component analysis of the cations affecting the tank water quality for site 1  
680 (Tank 1 and Prototype I) and 2 (Tank 2-FF and Prototype II). The directionality of the arrows  
681 indicate the correlation (same = positive; opposite = negative) between the different variables  
682 and illustrate the predominant variables best describing the collected tank water samples.

683 **Fig. 3.** Box and whiskers plot illustrating the distribution of the intact cells or oocysts/100 mL  
684 recorded for each of the target organisms using EMA-qPCR (*E. coli*, enterococci, *Klebsiella*  
685 spp., *Legionella* spp., *Pseudomonas* spp. and *Salmonella* spp.) and PMA-qPCR  
686 (*Cryptosporidium* oocysts) in the tank water samples collected from **(A)** site 1 and **(B)** site 2.  
687 The whiskers at the end of each box indicate the minimum and maximum values, while the  
688 box is defined by the lower and upper quartiles and the mean value.